



ISWX E2

$U_w = 1,2 \text{ W/m}^2\text{K}^*$

GLAZING UNIT

$U_g = 1,0 \text{ W/m}^2\text{K}$



GLAZING UNIT

double glazing

- gas - argon
- warm spacer
- low emission coat
- toughened pane



4H/16/4T (AR)
 $U_g = 1,0 \text{ W/m}^2\text{K}$

PRODUCT CHARACTERISTICS

- ✓ profile made of high-quality, glued pine wood, painted 3 times
- ✓ warm carpentry color - natural pine
- ✓ skylight is extremely tight thanks to 4 seals
- ✓ safe handle with key and micro-ventilation function
- ✓ fashionable color of the flashing - RAL 7016
- ✓ wide range of installation angle 15-65°
- ✓ skylight for non-habitable areas
- ✓ can be installed with additional sealing accessories
- ✓ wide range of internal blinds and pleats



15° - 65°

GUARANTEE

- ✓ 2 years guarantee (detailed conditions are available on the website www.okpol.pl)



AVAILABLE SIZES

Glazing area [m ²]	0,23
Symbol size	01
Window sizes: width x height [cm]	55x78



30°



180°

* U_w parameter - window thermal transmittance coefficient given for reference sizes of 1.23 (±25%)m x 1.48 (-25%)m, calculations according to EN ISO 10077-1 / EN ISO 10077-2